BibTool Quick Reference Card

for BibTool version 2.60 — see also `http://www.gerd.neugebauer.de/software/TeX/BibTool/`

©2015 Gerd Neugebauer (gene@gerd-neugebauer.de)

Command line options

-- *rsc_command*
: Perform resource command as if given in a file.

-A *type*
: Determine key disambiguation. *type* in `0`, `a`, `A`,

-d
: Check double entries.

-f *key_format*
: Generate keys according to *key_format*

-F
: Enable key generation with free key format.

-h
: Print short help and exit.

-i *input_file*
: Mark a file to be processed later.

-k
: Make keys with the short format.

-K
: Make keys with the long format.

-o *output_file*
: Send the output to *output_file*.

-q
: Suppress warning messages.

-r *resource_file*
: Read the resource file *resource_file*.

-R
: Load the default resource file now.

-s
: Sort the result.

-S
: Sort the result in reverse order.

-v
: Turn on verbose messages about the actions performed.

-x *aux_file*
: Extract those entries mentioned in *aux_file*.

-X *regex*
: Extract entries matching *regex*.

Libraries

`check_y`	Check the value of the year.
`default`	All default settings.
`field`	Redefine field names.
`brace`	Use braces as delimiters.
`improve`	Apply improvements.
`iso2tex`	Translate ISO 8859/1 characters.
`iso_def`	Define ISO 8859/1 characters for formatting.
`month`	Introduce strings for month names.
`opt`	Remove OPT in field names.
`sort_fld`	Specify sort order for fields.
`tex_def`	Define TeX macros for formatting.
`biblatex`	Capitalize fields known to bibLaTeX.

General

resource.search.path = {dir_1:dir_2...}
resource {*file*}
bibtex.search.path = {dir_1:dir_2...}
bibtex.env.name = {*ENV_NAME*}
env.separator = {*c*}
dir.file.separator = {*c*}
print {*message*}
quiet = *OnOff*
verbose = *OnOff*
crossref.limit = {*n*}

Reading and Printing

input {*bib_file*}
output.file = {*file*}
pass.comments = *OnOff*
new.entry.type {*type*}
print.align = *n*
print.align.key = *n*
print.align.preamble = *n*
print.align.comment = *n*
print.braces = *OnOff*
print.comma.at.end = *OnOff*
print.deleted.entries = *OnOff*
print.deleted.prefix = {*prefix*}
print.indent = *n*
print.line.length = *n*
print.newline = *n*
print.parentheses = *OnOff*
print.terminal.comma = *OnOff*
print.use.tab = *OnOff*
print.wide.equal = *OnOff*
suppress.initial.newline = *OnOff*
new.field.type {*new=old*}
symbol.type = *type*
: upper, lower, cased

Sorting

sort = *OnOff*
sort.cased = *OnOff*
sort.reverse = *OnOff*
sort.format = {*format*}
sort.order {...}
sort.macros = *OnOff*

Searching (Extraction)

tex.define {*macro[arg]=text*}
extract.file {*file*}
select {$field_1$...$field_n$ "*regex*"}
select {$type_1$...$type_n$ }
select.by.string {$field_1$...$field_n$ "*regex*"}
select.by.string.ignore {*chars*}
select.case.sensitive = *OnOff*
select.fields = {$field_1$,$field_2$,...}

Field Manipulation

add.field {*field=value*}
delete.field {*field*}
rewrite.rule { *pattern* }
: delete all matching fields

rewrite.rule { *pattern # replacement*}
: rewrite all fields

rewrite.rule {f_1...f_n *# pattern # replacement*}
: rewrite some fields

rewrite.case.sensitive = *OnOff*
rewrite.limit = {*n*}

Checks

check.double = *OnOff*
check.do.delete = *OnOff*
check.rule {*field # pattern # message*}
check.case.sensitive = *OnOff*

Strings

macro.file {*file*}
print.all.strings = *OnOff*
expand.macros = *OnOff*
expand.crossref = *OnOff*

BibTeX1.0

apply.alias = *OnOff*
apply.include = *OnOff*
apply.modify = *OnOff*
key.make.alias = *OnOff*

Counting

count.all = *OnOff*
count.used = *OnOff*

Key Generation

preserve.keys = *OnOff*
preserve.key.case = *OnOff*
key.format = {*format*}
special values: short, long, short.need, long.need, empty
key.generation = *OnOff*
default.key = {*key*}
key.base = *base*
values: upper, lower, digit
key.number.separator = {*s*}
key.expand.macros = *OnOff*
fmt.name.title = {*s*}
fmt.title.title = {*s*}
fmt.name.name = {*s*}
fmt.inter.name = {*s*}
fmt.name.pre = {*s*}
fmt.et.al = {*s*}
fmt.word.separator = {*s*}
new.format.type = {*n*="*spec*"}

Name Formatting Specification

Use *n* letters. Use *m* name parts. Insert *pre* before, *mid* between, and *post* after the words. Translate according to the s parameter ('+', '-', '*').

%*sn.m*f[*mid*][*pre*][*post*]
format first names.
%*sn.m*v[*mid*][*pre*][*post*]
format "von" part.
%*sn.m*l[*mid*][*pre*][*post*]
format last name.
%*sn.m*j[*mid*][*pre*][*post*]
format "junior" part.

Format Specifications

Pseudo fields:

$key
$default.key
$sortkey
$source
$type
@type
$day
$month
$mon
$year
$hour
$minute
$second
$user
$hostname

Formatting Fields:

%±*x.y* n(*field*)
format *y* characters of *x* last names.
%±*x.y* N(*field*)
format *y* characters of *x* names.
%±*x.y* p(*field*)
format *x* names according to the name format *y*.
%±*x.y* d(*field*)
format at most *x* digits of the y^{th} number.
%±*x.y* D(*field*)
format *x* digits of the y^{th} number without truncation.
%±*x* s(*field*)
format *x* string characters.
%±*x.y* t(*field*)
format *x* sentence words of length *y*.
%±*x.y* T(*field*)
format *x* sentence words of length *y*. (Words ignored)
%±*x.y* w(*field*)
format *x* words of length *y*.
%±*x* W(*field*)
format *x* words of length *y*. (Words ignored)
%±*x.y* #n(*field*)
test whether the number of names is between *x* and *y*.
%±*x.y* #N(*field*)
test whether the number of names is between *x* and *y*.
%±*x.y* #p(*field*)
test whether the number of names is between *x* and *y*.
%±*x.y* #s(*field*)
test whether the number of characters is between *x* and *y*.
%±*x.y* #t(*field*)
test whether the number of words is between *x* and *y*.
%±*x.y* #T(*field*)
test whether the number of not ignored words is between *x* and *y*.
%±*x.y* #w(*field*)
test whether the number of words is between *x* and *y*.
%±*x.y* #W(*field*)
test whether the number of not ignored words is between *x* and *y*.